

Xtreme[®] Seam Tape



Product Description:

Tex-Trude Xtreme Tape is composed of a 23 mil thick strong self-adhering polymer asphalt adhesive that has superior performance and is designed to seal the seams of the Xtreme Vapor Barrier Systems. It is also used to seal penetrations coming through the slab, small repairs, and patch areas.



Installation:

Prior to installation, perform a visual inspection of the Xtreme Vapor Barrier to insure a 6" overlap has

been achieved and all dust, dirt, debris, moisture has been removed.

Slab Penetration: Using Xtreme Vapor Barrier material, cut out a minimum of 12" and one-half times the pipe circumference. Cut slits in the boot half the width of the film. Slide the boot over the penetration. The boot is to be in flat contact with the Xtreme Vapor Barrier. It is important to tape the boot to the pipe and around the base.

Warm conditions: Store out of direct sunlight. Perform normal installation, using industry knowledge of the guidelines for vapor barriers.

Cold conditions: In cold weather applications, it is suggested to condition the tape 8 hours in a warm environment prior to use. This will help the tape reach its optimal performance.

Limited Warranty:

Tex-Trude warrants this product to meet the published specifications and to be free of defects in

workmanship and materials at the time of shipment from our factory. If any Xtreme material proves to contain manufacture defects that substantially affect the performance, then Tex-Trude will at their option replace the material or refund the purchase price. This limited warranty is the only warranty offered by Tex-Trude, LP as it relates to Xtreme products. There are no other warranties, including the implied warranties of merchantability or fitness for a particular purpose. Tex-Trude specifically disclaims liability for any incidental, consequential, or other damages.



Tex-Trude, LP
2001 Sheldon Road
Channelview, Texas 77530
P- 281/ 452-5961
F- 281/ 452-5642
www.tex-trude.com

TECHNICAL DATA	
	Xtreme Tape
Thickness	23 mil
Permeance	0.01
Tensile Strength	1112 psi
Elongation	1058.466%
Cold Weather Resistance	Excellent

PACKAGING	
	Xtreme Tape
Size	4" x 150'
Rolls Per Case	9
Weight	6.8 lb ea. 61.2 lbs per case
Color	Off White

ISO 9001 – 2008 CERTIFIED

TEX-TRUDE, LP TECHNICAL DATA SHEET